

TECHNICAL SPECIFICATION



EVO® VISTA^{lens}® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented

White / Smoke / AMF270-405-F00



DESCRIPTION

EVO® VISTA^{lens}® DUALSWITCH™ combines the new EVO® VISTA® retractable eyewear helmet technology with the innovative DUALSWITCH™ chinstrap harness system, making it simple to change between working at ground level and working at height safety standards.

The EVO® VISTA^{lens}® DUALSWITCH™ helmet incorporates a fully retractable optical class 1 integrated overspec offering B-RATED impact protection even at extreme temperatures.

OPTIONS

White / Smoke (AMF270-405-F00)

Orange / Smoke (AMF270-401-J00)

White / Smoke Badge (AMF279-M05-F00)

Yellow / Smoke (AMF270-409-H00)

SAFETY STANDARDS

EN 12492 • EN 397 • EN 50365 • EN 166 • EN 170 • ANSI
Z87. 1 • ANSI/ISEA Z89.1 Type I



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






























Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 3 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

| | | | |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Peak Micro |  | Impact Resistance 100 Joules |
|  | Side Impact Resistance 25 Joules |  | Molten Metal Yes |
|  | Lateral Deformation Yes |  | EN 50365 ELECTRICAL INSULATION 1000V |
|  | Maximum Temperature +50°C |  | Minimum Temperature -40°C |
|  | ABS Shell Yes |  | EPP Liner Yes |
|  | Recyclable Shell |  | Textile Harness |
|  | Ventilation Yes |  | Depth Adjustment 3D Harness |
|  | Wheel Ratchet Yes |  | Fitted 4 point DualSwitch chinstrap (EN12492 and EN397 compliant) Fitted |
|  | Universal Accessories Slot Yes |  | Reflective Option Fitted |
|  | BSI Kitemark Yes |  | JSPCheck Yes |
|  | RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C |  | LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2 |
|  | Manufacturer's Trademark JSP Dagger |  | Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1 |
|  | Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. B |  | The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T |
|  | Resistance to Surface Damage by Fine Particles (optional) K |  | Resistance to fogging (optional) N |
| | Lens Length 9cm |  | Product Weight 584.2 g |

FEATURES



Switch Down

The chinstrap release force of EN 12492 is greater than 500 Newtons. This limits the risk of losing the helmet during a fall.



Switch Up

The chinstrap release force of EN 397 is between 150 and 250 Newtons. This limits the risk of choking, the chinstrap has been designed to release if snagged.



Head Protection

EVO® VISTA® DUALSWITCH™ conforms to EN 397 and EN 12492. The safety cell concept prevents ricocheting debris travelling up the

JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 3 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



eyewear and impacting the scalp. In addition, the eyewear cannot make contact with the scalp, preventing injury should the eyewear be forced back on to the safety cell.



Secure Comfort

Now available with EVO® VISTA® DUALSWITCH™, the Revolution® Flex wheel ratchet harness eliminates pressure points for extreme comfort and features a Chamlon™ cotton sweatband. Ventilation reduces helmet temperatures by an average 2-3 degrees.



EPP Liner

Our robust Expanded Polypropylene (EPP) liner ensures class leading impact attenuation, offering side, front and rear impact protection, as required by EN 12492.




ID Card Holder

Specially engineered attachment points on the helmet enable secure fitting of an ID card holder. The clear polycarbonate holder uses a simple push and slide mechanism to fit a standard size business card.



CR2 Reflectivity

CR2 is a high intensity reflective material offering, on average, 60% more reflectivity than standard reflective clothing. CR2 is optional.



Eye Protection

EVO® VISTAlens® eye protection is made with optical class 1 material for a panoramic view with minimal distortion. The integrated eyewear offers B-rated impact resistance and UV filtering, with anti-mist and anti-scratch coatings.



Adjustable Seal

The EVO® VISTAlens® overspec is fully adjustable to optimise fit and compatibility with prescription spectacles. The thermoplastic rubber seal moulds to the wearer's face, enhancing comfort and projectile protection.



Ventilation

The shell and internal liner are vented to increase comfort and allow a cooling air flow, reducing helmet temperatures by an average 2-3°C.



Compatibility

The EVO® VISTAshield® and EVO® VISTAlens® helmets have been specifically designed to maximise compatibility with other JSP PPE, including the Force®8 half mask with PressToCheck™ filters and the Sonis® mounted ear defender range.



Bespoke Branding

The EVO® VISTA® DUALSWITCH™ range can be customised to meet a corporate identity. Helmets can also be printed with a company logo to improve brand recognition and discourage theft. MOQs apply.

LOGO

- Front
- Back

RANGE



VIDEOS

- www.youtube.com/watch?v=MkYerVOVfoc
- www.youtube.com/watch?v=wG8UFDHA-b8&t=9s
- www.youtube.com/watch?v=GN02TNNZyz4&t
- www.youtube.com/watch?v=GoHnouWARu4
- www.youtube.com/watch?v=i8-pUrlrl1o
- vimeo.com/398195919/

DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-evo-vistalens-dualswitch.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 3 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

